

Metric Conversion

- Capacity (kg.)	A Overall Span (mm)	B Span Between Wheels	C Clearance Span	D Max. Height Under Beam	D Min. Height Under Beam	E I-Beam Depth	F Wheel Tread	G Caster Dia. (4 Pos.) Locking	- Est. Weight (kg)	- Model #
1,815	2438.4	2159	2082.8	2438.4	1676.4	2438.4	1568.45	152.4	137.89	4P88
	2438.4	2159	2082.8	3048	2286	2438.4	1568.45	152.4	154.22	4P810
	2438.4	2159	2082.8	3657.6	2895.6	3048	1568.45	152.4	162.84	4P812
	3048	2768.6	2692.4	2438.4	1676.4	3048	1568.45	152.4	152.86	4P108
	3048	2768.6	2692.4	3048	2286	3048	1568.45	152.4	169.64	4P1010
	3048	2768.6	2692.4	3657.6	2895.6	3048	1568.45	152.4	177.81	4P1012
	3657.6	3378.2	3302	2438.4	1676.4	3657.6	1568.45	152.4	175.09	4P128
	3657.6	3378.2	3302	3048	2286	3657.6	1568.45	152.4	191.42	4P1210
	3657.6	3378.2	3302	3657.6	2895.6	3657.6	1568.45	152.4	199.58	4P1212
	4572	4292.6	4216.4	2438.4	1676.4	3657.6	1568.45	152.4	189.6	4P158
	4572	4292.6	4216.4	3048	2286	3657.6	1568.45	152.4	201.85	4P1510
	4572	4292.6	4216.4	3657.6	2895.6	3657.6	1568.45	152.4	214.1	4P1512
	Options	Cart Assembly must be purchased at time or order. (<i>Retrofit not available</i>)								9
Caster Brakes									CB	
Kick Stand Assembly must be purchased at time or order. (<i>Retrofit not available</i>)									KSA	
Custom Hole Spacing's									CHS	
Swirled Finish's must be purchased at time or order. (<i>Retrofit not available</i>)									SF	
Custom I -Beam Lengths									IBL	
Custom Heights									CH	