

Metric Conversion

-	A	B	C	D	D	E	F	G	-	-
Capacity (kg)	Overall Span (mm)	Span Between Wheels	Clearance Span	Max. Height Under Beam	Min. Height Under Beam	I-Beam Depth	Wheel Tread	Caster Dia. (4 Pos.) Locking	Est. Weight (kg)	Model #
907	1828.8	1524	1498.6	2743.2	1879.6	152.4	1397	152.4	93.44	A2P69
	1828.8	1524	1498.6	3048	2184.4	152.4	1397	152.4	95.25	A2P610
	1828.8	2133.6	2108.2	2743.2	1879.6	152.4	1397	152.4	97.98	A2P89
	1828.8	2133.6	2108.2	3048	2184.4	152.4	1397	152.4	99.34	A2P810
	1828.8	2133.6	2108.2	3657.6	2794	152.4	1397	152.4	115.67	A2P812
	3048	2743.2	2717.8	2743.2	1879.6	152.4	1397	152.4	106.14	A2P109
	3048	2743.2	2717.8	3048	2184.4	152.4	1397	152.4	107.5	A2P1010
	3048	2743.2	2717.8	3657.6	2794	152.4	1397	152.4	123.83	A2P1012
	3657.6	3352.8	3327.4	2743.2	1879.6	203.2	1397	152.4	117.93	A2P129
	3657.6	3352.8	3327.4	3048	2184.4	203.2	1397	152.4	119.29	A2P1210
	3657.6	3352.8	3327.4	3657.6	2794	203.2	1397	152.4	135.62	A2P1212
	4572	4267.2	4241.8	2743.2	1879.6	254	1397	152.4	142.88	A2P159
	4572	4267.2	4241.8	3048	2184.4	254	1397	152.4	144.7	A2P1510
	4572	4267.2	4241.8	3657.6	2794	254	1397	152.4	161.03	A2P1512
Options	Cart Assembly								9	CA15
	Caster Brakes									CB
	Kick Stand Assembly									KSA
	Custom Hole Spacing's									CHS
	Swirled Finish's									SF
	Custom I -Beam Lengths									IBL
	Custom Heights									CH