



ALUMINUM CONSTRUCTION - LOW HANDLE EFFORT

MODEL PA

PA Model Ratchet Lever Hoist

COFFING PA Model - Aluminum ratchet lever hoists provide high quality and durability. The PA's extremely low handle effort and 360° rotating handle make it easy to operate, and the one-handed free chaining mechanism provides easy rigging. The PA is ideal for construction and commercial applications.

CAPACITIES & LIFT - Rated loads of 3/4, 1, 1 1/2, and 3 Tons, with 5, 10, 15, and 20 foot standard lifts.

RUGGED AND LIGHTWEIGHT - Unit and handle made from high strength ductile aluminum alloy. Compact design increases portability and rigging efficiency.

EASY TO USE - Double reduction gearing and short handle provide lowest handle effort in the Coffing line.

360° ROTATING HANDLE - Provides versatile rigging options when used in confined spaces.

EASY FREE CHAINING - State-of-the-art free wheeling mechanism allows quick and easy one-handed take-up and positioning of slack chain.

POSITIVE LOAD CONTROL - Enclosed self-adjusting screw-and-disc type load brake stays clean and dry — eliminating drift and backlash for safe, sure holding. Screw-and-disc brake lowering allows “micro-inching” load positioning.

LOW MAINTENANCE - Hardened steel load chain provides high strength and resists wear. Alloy steel spur gearing is heat-treated for long life and is lifetime lubricated.

LIFETIME WARRANTY



3/4 - 3 Ton

● SPECIFICATIONS ●

PA Model Ratchet Lever Hoists

Capacity		Model Number	Lift (ft.)	Strands of Load Chain	Minimum Dist. Between Hooks (in.)	Handle Length (in.)	Average Handle Effort (lb.)	Net Weight (lb.)
(lb.)	(Ton)							
1500	3/4	PA-1500	5	1	12	12	37	15
1500	3/4	PA-1510	10	1	12	12	37	17
1500	3/4	PA-1515	15	1	12	12	37	19
1500	3/4	PA-1520	20	1	12	12	37	21
2000	1	PA-2000	5	1	13	12	49	15
2000	1	PA-2010	10	1	13	12	49	17
2000	1	PA-2015	15	1	13	12	49	19
2000	1	PA-2020	20	1	13	12	49	21
3000	1 1/2	PA-3000	5	1	14 1/2	12	41	25
3000	1 1/2	PA-3010	10	1	14 1/2	12	41	29
3000	1 1/2	PA-3015	15	1	14 1/2	12	41	33
3000	1 1/2	PA-3020	20	1	14 1/2	12	41	37
6000	3	PA-6000	5	2	17 1/2	16	61	41
6000	3	PA-6010	10	2	17 1/2	16	61	48
6000	3	PA-6015	15	2	17 1/2	16	61	55
6000	3	PA-6020	20	2	17 1/2	16	61	62

Note: For complete dimensional data, refer to Coffing Dimensional Databook

COFFING®
HOISTS