



MODEL  
**A / AD**

MODEL  
**GT**



3/4 - 1 1/2 Ton

Made in USA

## A & AD Ratchet Lever Load Binders

**COFFING A and AD Models** - Roller chain load binders provide quality and durability. Unlike over-center binders, the ratchet and pawl design protects the operator by providing incremental take-up for proper tensioning and securing of the load.

**CAPACITIES & LIFT** - Rated loads from 3/4 to 1 1/2 Tons. For standard lift, see chart below.

**CONVERTIBLE** - Double-chain model converts to single-chain.

**LIFETIME WARRANTY**

### • SPECIFICATIONS •

A & AD Ratchet Lever Load Binders

Load Limits		Ultimate Strength (lb.)	Model	Std. Reach (in.)	Strands of Load Chain	Minimum Dist. Between Hooks (in.)	Handle Length (in.)	Take-Up Increments (in.)	Net Weight (lb.)
Working (lb.)	Proof (Ton)								
1500	3000	7500	<b>A</b>	19 1/2	1	15 1/2	19 1/4	5/8	11 1/2
3000	6000	15000	<b>AD</b>	20	2	16 3/4	19 1/4	5/16	14 1/2

**COFFING**<sup>®</sup>  
HOISTS

RATCHET LOAD BINDERS / PULLERS



GT-1300-32

GT-2000-65

GT-3500-32

## GT Model Wire Rope Lever Tool

**COFFING GT Models** - Designed for heavy-duty pulling, rigging, dragging, stretching and lifting applications. Its versatility and ability makes it perfect for use in the construction and transportation industries, as well as hundreds of other industrial applications. Coffing GT models are lightweight, compact and built tough for long life and trouble-free service.

**CAPACITIES** - Rated loads from 1 to 3 Tons. 32 ft. of wire rope on 1 and 3 Ton models / 65 ft. of wire rope on 2 Ton models

**SMOOTH OPERATION** - Large surface area of dual clamping jaws provide an evenly distributed grip for smooth operation and low wear.

**LIFETIME WARRANTY**

### • SPECIFICATIONS •

GT Wire Rope Lever Tool

Model	Rated Capacity (Tons)	Product Code	Standard Wire Rope Length (ft.)	Wire Rope Diameter (in.)	Lever Length Extended (in.)	Lever Length Retracted (in.)	Rope Advance † (in.)	Overall Dimensions (in.)	Net Weight * (lb.)	Net Weight ** (lb.)
<b>GT-1300-32</b>	1	0013	32	5/16	29.1	21.3	1.30	19.7 x 9.1 x 4.0	35	18
<b>GT-2000-65</b>	2	0020	65	7/16	29.1	21.3	1.45	24.8 x 13.0 x 5.9	79	40
<b>GT-3500-32</b>	3	0035	32	5/8	29.1	21.3	0.78	28.6 x 12.8 x 7.0	94	66

† Per full stroke at rated load

\* Wire rope included

\*\* Less Wire Rope